

Temperature Sensing Crystals Unit YSX211TS




Applications

- Mobile Communications

Features

- Excellent Reliability Characteristics Such as Heat and Mechanical Shock
- Pb-free and Satisfy ROHS Requirements



Specifications (规格参数)

Item/Type	Specifications
Output Frequency Range 额定频率范围	19.2 ~ 54MHz
Operating Temperature Range 工作温度	-30 ~ +85°C, or specify
Storage Temperature Range 储存温度	-40 ~ +85°C
Frequency Tolerance (at 25°C) 频率偏差	±10ppm, or specify
Frequency Stability Over Operating Temperature Range 频率-温度特性	±10ppm, or specify
Shunt Capacitance (C0) 静态电容	3pF Max
Drive Level 激励电平	1~200μW (50μW typical)
Load Capacitance 负载电容	8pF, 10pF, 12pF, or specify
Aging (at 25°C) 老化率	± 3ppm / first year Max
Thermistor Resistance (at 25°C) 热敏电阻	100KΩ ±1%
Thermistor B-constant (25~50°C) 热敏电阻B常数	4250KΩ±1%

Equivalent Series Resistance (等效串联电阻 (ESR))

Frequency Range	ESR
19.2 ~ 30MHz	100Ω Max
30 ~ 54MHz	80Ω Max

Temperature Sensing Crystals Unit YSX211TS



Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)										
<p>Top View</p> <p>Bottom View</p> <p>Side View</p>	<table border="1"> <thead> <tr> <th data-bbox="898 781 1182 819">Pin</th> <th data-bbox="1182 781 1466 819">FUNCTION</th> </tr> </thead> <tbody> <tr> <td data-bbox="898 819 1182 853">#1</td> <td data-bbox="1182 819 1466 853">Xtal Terminal (Input)</td> </tr> <tr> <td data-bbox="898 853 1182 887">#2</td> <td data-bbox="1182 853 1466 887">Thermistor Terminal + GND</td> </tr> <tr> <td data-bbox="898 887 1182 920">#3</td> <td data-bbox="1182 887 1466 920">Xtal Terminal (Output)</td> </tr> <tr> <td data-bbox="898 920 1182 954">#4</td> <td data-bbox="1182 920 1466 954">Thermistor Terminal</td> </tr> </tbody> </table>	Pin	FUNCTION	#1	Xtal Terminal (Input)	#2	Thermistor Terminal + GND	#3	Xtal Terminal (Output)	#4	Thermistor Terminal
Pin	FUNCTION										
#1	Xtal Terminal (Input)										
#2	Thermistor Terminal + GND										
#3	Xtal Terminal (Output)										
#4	Thermistor Terminal										